



VBG VBG Group AB, Sweden
 Type: 8040 Part: 08-0200
 No: XXXXXX XX/XX
 Class: S (E4)
 Approval: 55R-01 0066

D	136	kN
Dc	-	kN
S	-	kg
V	-	kN

VBG

TYPE 8040
 PART 09-1862
 NO. NO.YEAR/WEEK

VBG GROUP TRUCK EQUIPMENT AB

3 Coupling center distance "L3" depends on pretension and drawbeam thickness (see table)

Drawbeam thickness	L3	
	P=16	P=21
16	204	209
20	208	213
22	210	215
28	216	221
30	218	223
32	220	225

- 2 Mounting dimensions acc. to ISO 3584:2001 category 5-7.
- 1 Dimensions for indormation only. Tolerance ±10 mm.

EXTERNAL DISTRIBUTION

VBG GROUP

Description Coupling VBG 8040 Koppling VBG 8040	Modified Date	Modified by	Modification No.	Issue
	2016-02-01	HB	12613	e
	3D Model No.	Engineer		Checked by
	08-020000	KP		
Sheet Size	Scale	Projection	Drafting Date	Drafted by
A3	1:5	⊕	2006-05-17	KP
Stage	Drawing No.			
P	08-020000 (F) INFO			
This drawing is the property of VBG Group AB and is protected in accordance with prevailing law. Changes must be made in CAD-program, this concerns both 2D & 3D.				