



3 Coupling center distance "L3" depends of pretension and drawbar thickness (see table)

Drawbeam thickness	L3	
	P=16	P=21
16	204	209
20	208	213
22	210	215
28	216	221
30	218	223
32	220	225

2 Mounting dimensions acc. to ISO 3584:2001 category 5-7

1 Measures for information only. Tolerance ±10mm.

EXTERNAL DISTRIBUTION

VBG
 TYPE 8500
 PART 09-1863
 NO. NO. YEAR/WEK

VBG GROUP TRUCK EQUIPMENT AB

VBG VBG Group AB, Sweden
 Type: 8500 Part: 09-0090
 No: XXXXXX XX/XX

D	190	kN
Dc	-	kN
S	-	kg
V	-	kN

Class: C 50-X **E4**
 Approval: 55R-01 0067



VBG GROUP

Description
 Coupling VBG 8500
 Koppling VBG 8500

Modified Date	Modified by	Modification No.	Issue
2016-05-09	HB	12613	g
3D Model No.	Engineer	Checked by	
08-009000	KP		
Sheet Size	Scale	Projection	Drafting Date
A3	1:5		2006-04-04
Stage	Drawing No.	Drafted by	
P	08-009000 (F) INFO	KP	

This drawing is the property of VBG Group AB and is protected in accordance with prevailing law. Changes must be made in CAD-program, this concerns both 2D & 3D.